

HYUNDAI

5" Outdoor Medium Speed PTZ

5MP

H.265 PTZ Outdoor Medium Speed IR 240M

Model: HY-SS500PL

5MP

H.265

IP66

IR
CUT

ONVIF

Features:

- 5MP Outdoor Medium Speed PTZ
- 1/2.8" SONY Stravis Back-illuminated CMOS sensor
- H.264/H.265 Compression Method
- 36X Optical Zoom (5.3-130mm F1.6-F4.3)
- IR Distance 240m Max
- IP66 Outdoor Weatherproof
- Support POE (Optional)
- Support 36X Optical Zoom
- Support IP66 Weatherproof
- Support ONVIF, SLINK protocol



Specifications:

Model	HY-SS500PL
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H265
S/N Ratio	60db
PTZ	
Horizontal Rotation Speed	200°/sec
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	100°/s
Tilt Rotation Range	0°~90°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max. 20 points
Lens	
Focus Length	5.3-130mm F1.6-F4.3
Focus Control	36X Optical Zoom
Infrared LED	
Infrared LED	φ 35 x 11PCS IR LEDS + 4PCS LED Laser
IR Range	240m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support Profile S,Profile G,Profile T
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2592*1944@20fps
Main Stream2	2560*1440@25fps
Main Stream3	1920*1080@30fps
Main Stream4	1280*720@30fps
Main Stream5	/
Main Stream6	/
Sub Stream1	720*480@20fps
Sub Stream2	352*288@20fps
Sub Stream3	/
Sub Stream4	/
Interface	
Audio	Optional
Alarm	/
SD Card Slot	Optional
POE	/
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 5A
Lightning Protection	Transient voltage 6000V
Dimension	33x33x52(cm)
Weight	3.9Kgs