

HYUNDAI

4 CH NVR



Model: HY-Q4H16

- 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P) real time recording;
- Max 4 ch playback synchronously
- Onboard 1 SATA ports , one supports 6 TB
- Built-in high-power switching power supply
- Alarm audio and talk-back supported
- ONVIF 2.4 supported and compatible with almost all third-party IP cameras
- Up to 5 Mega pixels IP camera recording
- PTZ control via USB Mouse
- VGA, HDMI® and CVBS output sync
- HDMI® and VGA resolution up to 1920×1080P
- Built-in P2P Cloud service, firewall penetration automatically
- Always online , no need configuration for remote view anymore
- Mass of network protocols NTP, SADP, Camera Auto Discovery, Email, RTSP, UPNP
- Support iPhone, Android, Windows Mobile Phone, BlackBerry and Symbian APPs
- Internet Explorer, Chrome, Firefox, Safari and center monitoring client supported

Specification:

Model	HY-Q4H16
Recording Bandwidth	Max 40Mbps
Recording Resolution	5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Display Split	1/4
live/Playback performance	4K: 1ch realtime 4MP: 2ch realtime 2MP: 4ch realtime
Output Interface	1 HDMI (up to 4K), 1 VGA
Display Resolution	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 1680*1050, 1600*1200, 1900*1200, 2560*1440, 3840*2160
Alarm Input/out	4ch in / 1ch out
Ethernet	RJ-45 port (10/100M)
Smart Phone	iOS, Android
Internal HDD	1 SATA HDD, up to 6TB
RS485	no
e-Sata	optional
Line In	yes
USB	2x2.0 USB
ONVIF	yes
Power Supply	DC12V 2A
Dimension (W×D×H)	300X227X53mm