

HYUNDAI

8 CH NVR



Model: HY-Q8H16

- 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P) real time recording;
- Max 4 ch playback synchronously
- Onboard 1 SATA ports, one supports 6 TB
- Built-in high-power switching power supply
- Alarm audio and talk-back supported
- ONVIF 2.4 supported and compatible with almost all third-party IP cameras
- Up to 5 Mega pixels IP camera recording
- PTZ control via USB Mouse
- VGA, HDMI® and CVBS output sync
- HDMI® and VGA resolution up to 1920×1080P
- Built-in P2P Cloud service, firewall penetration automatically
- Always online, no need configuration for remote view anymore
- Mass of network protocols NTP, SADP, Camera Auto Discovery, Email, RTSP, UPNP
- Support iPhone, Android, Windows Mobile Phone, BlackBerry and Symbian APPs
- Internet Explorer, Chrome, Firefox, Safari and center monitoring client supported

Specification:

| | |
|---------------------------|---|
| Model | HY-Q8H16 |
| Recording Bandwidth | Max 60Mbps |
| Recording Resolution | 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P) |
| Display Split | 1/4 |
| live/Playback performance | 4K: 1ch realtime 4MP: 2ch realtime 2MP: 4ch realtime |
| Output Interface | 1 HDMI (up to 4K), 1 VGA |
| Display Resolution | 1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 1680*1050, 1600*1200, 1900*1200, 2560*1440, 3840*2160 |
| Alarm Input/out | 8ch in / 1ch out |
| Ethernet | RJ-45 port (10/100M) |
| Smart Phone | iOS, Android |
| Internal HDD | 1 SATA HDD, up to 6TB |
| RS485 | no |
| e-Sata | optional |
| Line In | yes |
| USB | 2x2.0 USB |
| ONVIF | yes |
| Power Supply | DC12V 2A |
| Dimension (W×D×H) | 300X227X53mm |