

HYUNDAI

16CH H.265+ NVR 2160P

H.265
HEVC
High Efficiency Video Coding

4K



Model: HY-NVR1601-4K

8MP

16CH

H.265

8TB


VGA
Support

ONVIF

Features:

- 8MP(4K), 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P) real time recording;
- Third-party Network Cameras Supported
- Up to 8MP Resolution Recording and Playback
- HD and VGA Output, HD Port up to 4K (3840x2160)
- Support H.265+/H.265/H.264+/H.264 Video Format
- Support 1 SATA up to 8TB Capacity

Dimensions:



Specifications:

Model		HY-NVR1601-4K
System		
Main Processor	ARM Cortex A7 Processor	
Operating System	Embedded LINUX	
Video		
Input	16CH(3840*2160,2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, etc)	
Output	1 VGA, 1 HD	
Audio		
Input	1 Port RCA	
Output	1 Port RCA(Linear, 1kΩ)	
Audio Bit Rate	64kbps	
Audio Compression standard	G711u, G711a, ADPCM_DVI4	
Intercom	support (two-way)	
Alarm		
Sensor Input	4	
Output	4	
Motion Detection	16 Channel, MD Zones: 396 (22 × 18)	
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output	
Display		
HD Output1	1024x768/60Hz, 1280x720/60Hz, 1280x1024/60Hz, 1920x1080/60Hz, 4K(3840x2160)/30Hz	
HD Output2	/	
VGA	1920x1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Display Split	16CHxD1/9CHxD1/8CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k	
Digital Zoom	YES	
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm	
Recording		
Video Compression	H265/H264/H265+/H264+	
Resolution	4k(3840×2160),5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1(720×576/720×480)	
Record Rate	PAL :4K@10x25fps,5MP@16×25fp,4MP@16×25fp,3MP@16×25fp,1080P@16×25fp, 960P@16×25fp,720P@16×25fp, D1@16×25fp NTSC: 4K@10x30fps,5MP@16×30fp,4MP@16×30fp,3MP@16×30fp,1080P@16×30fp, 960P@16×30fp, 720P@16×30fp, D1@16×30fp	
Record Mode	Manual\Timer\Motion Detection\Smart Alarm	

HYUNDAI

16CH H.265+ NVR 2160P

Playback & Backup	
Local Sync Playback	1CH 4K@30fps, 1CH 5MP@30fps,2CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps
Decode Capability	4CH 1080P(1920x1080)@30fps
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Event Alarm,Tag search
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom,tag,clip
Backup Mode	USB Device/Network
Network	
Interface	1xRJ45 10M/100M/1000M Adaptive Ethernet Interface
Incoming Bandwidth	100MB
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, p2p,PPPOE
Onvif Version	Support Onvif 2.8
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS
Cloud Support	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
POE	/
WIFI UI	/
Storage	
Interface Type	1 SATA Hard Disk Interface (3.5" SATA)
Capacity	Up to 8TB capacity
eSATA	/
General	
Language UI	Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese,Janpanese
USB Interface	2 USB 2.0 Interfaces
RS485	1port
Power Supply	DC12V 2A
Working Environment	-10~55°C10~90%
Dimension(W×D×H)	260*215*43(mm)