

4 CH XVR KIT



HY-4KIT5MP-ECO package

DVR	1x HY-XVR-4CH (5 IN 1)
Camera	4 x HY-4IN1 5MP Metal Bullet AHD Camera IR 30m
Cable	2 x 15m + 2 x 20m DC Cable 1x 1 to 4CH power cable splitter
Mouse	1xUSB 2.0 Mouse
Adaptor	1xDC12V/5A

Camera Model

HY-4IN1-5MP

Image Sensor	K03
DSP	FH8536H
Image Resolution	1080P / 960H
Effective Pixels	1920*1080
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
S/N Ratio	≥50dB
Scanning System	Progressive Scan

Lens

Focus Length	3.6mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	5M Pixels
Auto Iris Support	NO

Night Vision

Infrared LED	24μ x 6PCS Array LED
Infrared Distance	30M
IR Status	Under 5 Lux
IR Power On	Auto Control

Camera Features

Day/Night	YES
OSD Menu Language	YES
White Balance	AUTO / MANUAL
Gain Control	AUTO
Noise Reduction	3DNR
Picture Adjustment	YES
DWDR	YES
OSD Support	NO
UTC	YES

General

Housing	Metal IP66
Bracket	YES
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max

Power Source	DC12V±10%, 500mA
Dimension	200*60*60(mm)
Weight	450g
DVR Model	
HY-XVR-4CH	
System	
Main Processor	Hi3520D V400
Operating System	Embedded LINUX
Video	
Input	Analog: 4*5MN Network: 4*5MP/8*1080P/16*960P
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI/Network
Output	1HDMI,1 VGA
Audio	
Input	NO
Two-way Audio	NO
Output	NO
Display	
VGA	Resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
HDMI	4CH*5MN@25fps /4CH*3MN@25fps/4CH*1080p@25fps/4CH*720P@25fps
Display Split	4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.265
Record Rate	4CH*5MN@8fps/4CH*3MN@10fps/4CH*1080p@25fps/4CH*720P@25fps
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Decode Capability	4CH*5MN/4CH*4MN@8fps/4CH*3MN@10fps/4CH*1080p@25fps/4CH*720P@25fps
Sync Playback	Pure Analog: 4CH 5MN@8fps
Remote Playback	1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind
Smart Phone Playback	4 Channel
Backup Mode	USB Device/Network
Network	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
Web Browser	IE8-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows 7/Windows 8/Windows 10
Extra Stream	D1/CIF/(1~25fps)
Smart Phone	iPhone, ipad, Android ,Android pad
Hard Disk Driver	
Interface Type	1 SATA Interface
Capacity	2.5"/3.5" SATA, Up to 6TB
General	
Language	Chinese, English, Polish, Russian, Thai, Hebrew, Arabic, Farisa German, French, Turkic, Spanish, Italian, Hungarian, Romanian,Dutch, Greek
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V ≤6W (Without Hard Disk)
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	260*220*45(mm)
Weight	2kg (Without HDD)